



PULL DISC HARROW



Take a Picture of This QR Code With Your Smart Phone to See it in Action



FEATURES & BENEFITS

- Triple lug tug
- 1" angle pin welded solid through main frame for added strength
- Single wheels standard optional dual wheels available
- Sealed, self aligning bearings
- Center sweep option available
- 4" x 3" frame construction

SPECIFICATIONS / OPTIONS

Models	DHP8	DHP10	DHP12
Drawbar Horsepower Requirement	35-100 hp	45-100 hp	55-100 hp
Approximate Transport Width	8'-10"	10'-10"	12'-4"
Max Cultivation Width	8'-6"	10'-6"	12'
Mainframe Width	60"	93 1/2"	93 1/2"
Approximate Weight Load on Each Blade	85-95	84-94	82-92
Disc Blade Sizes and Types	20-22" Notched or Smooth	20-22" Notched or Smooth	20-22" Notched or Smooth
Disc Blade Spacing	7 1/2" or 9"	7 1/2" or 9"	7 1/2" or 9"
Disc Bearing Type	Greaseable & Triple Sealed Ball Bearings	Greaseable & Triple Sealed Ball Bearings	Greaseable & Triple Sealed Ball Bearings
Number of Bearings	8	12	12
Forward Gang Angle Adjustment	15, 16.5, 18, 19.5, 21	15, 16.5, 18, 19.5, 21	15, 16.5, 18, 19.5, 21
Rear Gang Angle Adjustment	12, 13.5, 15, 16.5, 18	12, 13.5, 15, 16.5, 18	12, 13.5, 15, 16.5, 18
Hitch	Pull-type w/ clevis & hole for 1 1/4" pin	Pull-type w/ clevis & hole for 1 1/4" pin	Pull-type w/ clevis & hole for 1 1/4" pin

Available Colors:

